

DATASHEET

## **Rockfon® Tropic**



### **Rockfon® Tropic**

- Smooth attractive white surface for various applications
- Class A sound absorption
- Full range of formats in semi-concealed and visible grid options
- Easy to clean with a vacuum

#### **Product Description**

- Stone wool tile
- Visible side: smooth white painted fleece
- Rear side: back fleece
- Painted edges

#### **Application Areas**

- Office
- Education
- Leisure
- Retail

Edge detail	Module size (mm)	Approximate weight (kg/m²)	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO <sub>2</sub> eq/m²)*	A1-C4 Full life cycle impact (kg CO₂ eq/m²)*
A15	600 x 600 x 15 1200 x 600 x 15	2.0	33%	cradle to cradle	1.99	2.45
	600 x 600 x 20	2.4	35%		2.49	3.09
	1200 x 600 x 20					
A24	600 x 600 x 15	2.0	33%	CERTIFIED Cradle to cradle	1.99	2.45
	1200 x 600 x 15				1.99	2.45
	600 x 600 x 20	2.4	35%		2.49	3.09
	1200 x 600 x 20					
	1800 x 600 x 20					
E15	600 x 600 x 15	2.2	35%	CERTIFIED STATES CONTROL OF THE CERTIFIED STATES CONTROL OF TH	2.33	2.93
	1200 x 600 x 15					
E24	600 x 600 x 15	2.2	35%	cradle to cradle	2.33	2.93
	1200 x 600 x 15					
	600 x 600 x 20	2.8	36%		2.74	3.52
	1200 x 600 x 20					


<sup>\*</sup> For full environmental impact disclosure, see our product EPDs available on rockfon.link/int-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



### **Performance**



Sound absorption  $\alpha_{\text{w}}\!\!:$  up to 1.00 (Class A)



1.00

1.00

125 Hz 250 Hz 500 Hz 1000 Hz 2000 Hz 4000 Hz 0.40 0.75 0.95 0.90 1.00 1.00

0.95

0.95

1.00

Absorption class NRC 0.95 Α 0.90 1.00 Α 1.00 1.00



Reaction to fire



Light reflection



Humidity and sag resistance

Up to 100% RH. No visible deflection in high humidity. C/0N



#### Cleaning

Vacuum



#### Hygiene

Stone wool provides no sustenance to microorganisms



#### Recyclability

Fully recyclable stone wool



0.90

0.90

#### Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:

1.00







#### Material Health

All materials used in Rockfon products are screened against the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with the safe fibre EU regulation and hold an EUCEB certification.

Edge / Thickness (mm) /

A,E: 15 / 200

A,E: 20 / 200

A: 20 / 200

0.60

# **Sounds Beautiful**